



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : PREMIUM CONVENTIONAL SAE 5W-20 Motor Oil

Product code : 785793

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Motor Oil

Details of the supplier of the safety data sheet

Valvoline LLC
100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Classification | Concentration (%) |
|--|------------|---------------------------------------|-------------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC | 64742-54-7 | Not a hazardous substance or mixture. | >=60.00 - < 70.00 |



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

| | | | |
|---|------------|-------------------|-------------------|
| Distillates (Petroleum), Hydrotreated Heavy Paraffinic | 64742-54-7 | Asp. Tox. 1; H304 | >=20.00 - < 30.00 |
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | Asp. Tox. 1; H304 | >=5.00 - < 10.00 |
| DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC | 64742-65-0 | Asp. Tox. 1; H304 | >=1.00 - < 1.50 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical
- Specific hazards during : Do not allow run-off from fire fighting to enter drains or water



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

| | |
|---|---|
| firefighting | courses. If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. |
| Hazardous combustion products | : carbon dioxide and carbon monoxide Hydrocarbons |
| Specific extinguishing methods | : Product is compatible with standard fire-fighting agents. |
| Further information | : Standard procedure for chemical fires. |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : Prevent further leakage or spillage if safe to do so. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. |
| Other information | : Comply with all applicable federal, state, and local regulations. |

SECTION 7. HANDLING AND STORAGE

| | |
|-------------------------|--|
| Advice on safe handling | : Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. |
| Materials to avoid | : No materials to be especially mentioned. |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|------------|-------------------------------------|---|-----------|
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | TWA | 5 mg/m3 Mist | OSHA Z-1 |
| | | TWA | 5 mg/m3 Inhalable particulate matter | ACGIH |
| | | TWA | 5 mg/m3 Mist | OSHA P0 |
| | | TWA | 5 mg/m3 Mist | NIOSH REL |
| | | ST | 10 mg/m3 Mist | NIOSH REL |
| | | PEL | 5 mg/m3 particulate | CAL PEL |

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : No data available

Odour Threshold : No data available



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

| | | |
|--|---|---|
| pH | : | No data available |
| Melting point/freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flash point | : | > 390 °F / > 199 °C |
| | | Method: Cleveland open cup |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Self-ignition | : | No data available |
| Upper explosion limit / Upper flammability limit | : | 6 %(V) Calculated Explosive Limit |
| Lower explosion limit / Lower flammability limit | : | 1 %(V) Calculated Explosive Limit |
| Vapour pressure | : | 0.0012 hPa (68 °F / 20 °C) Calculated Vapor Pressure |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |
| Density | : | 0.8620 g/cm ³ (60.01 °F / 15.56 °C) |
| Solubility(ies) | | |
| Water solubility | : | No data available |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | | |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | 50 mm ² /s (104 °F / 40 °C) |
| Oxidizing properties | : | No data available |

SECTION 10. STABILITY AND REACTIVITY



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

| | |
|------------------------------------|---|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : Stable under recommended storage conditions. |
| Possibility of hazardous reactions | : Product will not undergo hazardous polymerization. |
| Conditions to avoid | : excessive heat |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | No hazardous decomposition products are known. |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation

Result : Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

Assessment : Slight, transient irritation
Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result : No eye irritation
Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l
toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l
aquatic invertebrates
(Chronic toxicity)

Ecotoxicology Assessment
Short-term (acute) aquatic : Not classified based on available information.
hazard

Long-term (chronic) aquatic : Not classified based on available information.
hazard

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l
toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l
aquatic invertebrates
(Chronic toxicity)

Ecotoxicology Assessment
Short-term (acute) aquatic : Not classified based on available information.
hazard

Long-term (chronic) aquatic : Not classified based on available information.
hazard



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

Persistence and degradability

Components:

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n- : log Pow: Expected > 7
octanol/water

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological : No data available
information

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

California Prop. 65

 **WARNING:** Cancer - www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory

TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information : R0366793

NFPA:

HMIS III:



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

| | | | | | | | |
|--|---|---------------|----------|---------------------|----------|------------------------|----------|
| <p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p> | <table border="1"><tr><td>HEALTH</td><td>0</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p> | HEALTH | 0 | FLAMMABILITY | 1 | PHYSICAL HAZARD | 0 |
| HEALTH | 0 | | | | | | |
| FLAMMABILITY | 1 | | | | | | |
| PHYSICAL HAZARD | 0 | | | | | | |

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-20 Motor
Oil

Version: 1.8

Revision Date: 12/04/2019

Print Date:
12/19/2019

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System