



# SAFETY DATA SHEET

Revision Date: 10/30/2018

Issue Date: 09/30/2014

## 1. Identification Of The Substance / Preparation And Of The Company / Undertaking

Product Name	POWER TUBE RTV - BLACK
Recommended Use	Standard Acetoxy Silicone Sealant
Product Number	891.072
Manufactured For	Winzer Corporation 4060 E. Plano Parkway Plano, TX 75074
Company Phone	1-800-527-4126
24 Hour Emergency Phone	INFOTRAC 1-800-535-5053 (US & Canada)

## 2. Hazards Identification

### Label Elements

#### GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### Classification Of The Substance Or Mixture



Compressed Gas

GHS04



Skin Sensitization - Category 1

GHS07



Specific Target Organ Toxicity - Repeat Exposure - Category 2 (oral)

GHS08

#### Signal Word

**WARNING**

#### Hazardous Statement(s)

Contains gas under pressure; may explode if heated. May cause an allergic skin reaction May cause damage to blood through prolonged or repeated ingestion.

#### Precautionary Statement(s)

##### Prevention

Do not breathe vapors. Contaminated work clothing must not be allowed out of the workplace. Wash thoroughly after handling. Wear protective gloves.



<b>Response</b>	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. Get medical attention if you feel unwell.
<b>Storage</b>	Protect from sunlight. Store in a well-ventilated place.
<b>Disposal</b>	Dispose of contents and container in accordance with local and national regulations.

### 3. Composition / Information On Ingredients

**Chemical characterization** Mixture

Chemical Name	CAS number	%
1,1-Difluoroethane	75-37-6	<1
2-Butanone, O,O',O"- (methylsilyldiylne) trioxime	22984-54-9	<5
2-Butanone, O,O', O"- (ethenylsilyldiylne) trioxime	2224-33-1	<1
N-beta-(aminoethyl)-gamma aminopropyltrimethoxysilane	1760-24-3	<1
Methyltri (ethylmethylketoxime) silane isomers and oligomers	Not available	<1

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First Aid Measures

#### General Information

<b>Inhalation</b>	: If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problem or irritation persists.
<b>Skin Contact</b>	Wash exposed skin with soap and water for several minutes. If skin irritation or rash develops, seek medical attention.
<b>Eye Contact</b>	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice or attention.
<b>Ingestion</b>	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
<b>Most Important Symptoms/ Effects, Acute And Delayed</b>	May cause an allergic skin reaction in some individuals. Vapors may cause mild respiratory irritation. Repeated or prolonged contact may cause damage to the blood, cardiovascular, and hematological system.
<b>Indication Of Immediate Medical Attention And Special Treatment Needed</b>	None known.

### 5. Fire-Fighting Measures

<b>Suitable Extinguishing Media</b>	Use extinguishing media suitable for surrounding fire.
<b>Unsuitable Extinguishing Media</b>	No information available.
<b>Specific Hazards Arising from the Chemical</b>	: Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce very toxic, flammable formaldehyde; silicon oxides; carbon oxides. Exposure of containers to heat and flames can cause them to rupture often with violent force.



**Special Fire Fighting Procedures**

Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

**6. Accidental Release Measures****Personal Precautions, Protective Equipment, And Emergency Procedures**

Ventilate the area. Wear appropriate protective clothing and equipment.

**Environmental Precautions**

Report release as required by local and national regulations.

**Methods And Materials For Containment And Cleaning Up**

Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

**7. Handling And Storage****Precautions For Safe Handling**

Avoid contact with eyes and skin. Avoid breathing vapors or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

**Conditions For Safe Storage, Including Any Incompatibilities**

Will evolve methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Store in a cool, dry, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F.

**U.F.C. (NFPA 30B) Aerosol Level**

Level 1 Aerosol

**8. Exposure Controls / Personal Protection****Occupational Exposure Limits**

Chemical Name	Exposure Limit
1,1-Difluoroethane	1000 ppm TWA AIHA WEELs
2-Butanone, O,O', O''- (ethenylsilyldyne) trioxime	None established
2-Butanone, O,O',O''- (methylsilyldyne) trioxime	None established
N-beta-(aminoethyl)-gamma aminopropyltrimethoxysilane	None established
Methyltri (ethylmethylketoxime) silane isomers and oligomers	None established

**Individual Protection Measures, Such As Personal Protective Equipment****Eye/Face Protection**

Safety glasses are recommended if eye contact is possible.

**Skin/Body Protection**

Wear impervious gloves to avoid skin contact. Wear personal protection as needed to avoid skin contact.

**Respiratory Protection**

None under normal use conditions. For operations where the exposure limits may be exceeded, a NIOSH approved supplied air respirators recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

**Engineering Controls**

General ventilation should be adequate for normal use. For operations where the exposure limits may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.



## 9. Physical And Chemical Properties

### Physical and Chemical Properties

#### Appearance

Physical State Thick liquid under pressure

Color Black

Odor Slight odor

Odor Threshold Not determined

pH Not determined

Melting Point/Freezing Point Not determined

Initial Boiling Point And Range Not determined

Flash Point Not applicable

Evaporation Rate Not determined

Flammability (Solid, Gas) Not flammable in the foam aerosol test

#### Upper/Lower Flammability Or Explosive Limits

Flammability Limit - Lower (%) 3.7% (1,1-Difluoroethane)

Flammability Limit - Upper (%) 18% (1,1-Difluoroethane)

Explosive Limit - Lower (%) Not determined

Explosive Limit - Upper (%) Not determined

Vapor Pressure (mm Hg): Not determined

Vapor Density (AIR = 1) Not determined

Specific Gravity (H<sub>2</sub>O = 1) 1.04 (Liquid component)

Solubility (water) Not determined

Partition Coefficient: N-Octanol/Water Not determined

Auto-Ignition Temperature Not determined

Decomposition Temperature Not determined

Viscosity Not determined

VOC Content Not determined

## 10. Stability And Reactivity

Reactivity Not normally reactive.

Stable under normal storage and handling conditions.

### Chemical Stability

**Possibility Of Hazardous Reactions** : Forms toxic chemicals on contact with strong oxidizing agents, strong bases, and strong acids. Will evolve methyl ethyl ketoxime (MEKO) when exposed to water or humid air.

**Conditions To Avoid** Keep away from excessive heat, and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

**Incompatible Materials** Strong oxidizing agents, strong bases, and strong acids.

**Hazardous Decomposition Products** Burning may produce formaldehyde; silicon oxides; carbon oxides.



## 11. Toxicological Information

### Information On The Likely Routes Of Exposure

<b>Inhalation</b>	Vapors can irritate the throat and respiratory tract.
<b>Ingestion</b>	Swallowing may cause gastrointestinal disturbances.
<b>Skin Contact</b>	Contains 2-Butanone, O,O', O''- (ethenylsilylidyne) trioxime and 2-Butanone, O,O',O''- (methylsilylidyne) trioxime which may cause an allergic skin reaction.
<b>Eye Contact</b>	May cause mild irritation.

### Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LD50 Inhalation
Product ATE	> 2,000 mg/kg	> 2,000 mg/kg	>5 mg/L
1,1-Difluoroethane			437,500ppm/4h (rat)
2-Butanone, O,O',O''- (methylsilylidyne) trioxime	2,643 mg/kg (rat)	> 2,000 mg/kg (rat)	
2-Butanone, O,O', O''- (ethenylsilylidyne) trioxime	> 2,000 mg/kg (rat)	> 2,009 mg/kg (rat)	
N-beta-(aminoethyl)-gamma aminopropyltrimethoxysilane	1,897 mg/kg (rat)	> 2,000 mg/kg (rabbit)	>1.49 - < 2.44 mg/L/4 hr (rat)

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Chronic Health Hazards</b>	Contains 2-Butanone, O,O',O''- (ethenylsilylidyne) trioxime, 2-Butanone, O,O',O''- (methylsilylidyne) trioxime, and distillates (petroleum), straight-run middle which may cause damage to the blood, cardiovascular, and hematological system through prolonged or repeated exposure.
<b>Carcinogenicity</b>	None of the components listed is a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA

## 12. Ecological Information

<b>Eco-toxicity</b>	1,1-Difluoroethane: LC50 Fish 719.61 mg/L/ 96hr (Calculated) 2-Butanone, O,O',O''- (methylsilylidyne) trioxime: LC50 Oncorhynchus mykiss (rainbow trout) > 120 mg/L/ 96hr LC50 Daphnia magna (water flea) >120 mg/L/ 48hr N-beta-(aminoethyl)-gamma aminopropyltrimethoxysilane: LC50 Brachydanio rerio (zebrafish) 597 mg/L/ 96hr LC50 Daphnia magna (water flea) 81 mg/L/ 48hr
<b>Persistence and Biodegradability</b>	No data available for product.
<b>Bio-Accumulative Potential</b>	No data available for product.
<b>Mobility in Soil</b>	No data available for product.
<b>Other Adverse Effects</b>	No data available.

## 13. Disposal Considerations

<b>Waste treatment methods</b>	Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.
--------------------------------	--



**14. Transport Information**

U.S. DOT UN1950, Aerosols, 2.2  
IMDG UN1950, Aerosols, 2.2 LTD QTY

**15. Regulatory Information****National Inventories**

All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

**SARA 311/312 Hazard Categories**

Acute Health Hazard  
Chronic Health Star Hazard  
Fire Hazard  
Sudden Release of Pressure Hazard  
Reactive Hazard

Classified under OSHA Hazcom 2012 GHS  
as per Section 2 of this SDS.

**CERCLA**

This material, as supplied, does not contain substances with reportable quantities under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302), oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Chemical Name California Prop. 65	California Prop. 65
Cobalt titanite green spinel	Cancer
Methanol	Birth defects or other reproductive harm

**16. Other Information**

To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.