Classificati	Classification: Vinyl Tile/Concrete/Terrazzo Sealer			
n on Hazardous	ngredien	ts		
CAS	¥ %	OSHA (PEL)	TVL (ppm)	Other
r* 111-9	90-0 <6	50 ppm	50 ppm	N/A
78-5 <sup>-</sup>	-3 <3	N/E	N/E	N/E
Irritant. May cause skin and eye irritation. Avoid contact with skin and eyes.				
Slightly irritating	g.			
Prolonged or re skin.	peated co	ntact may cause	irritation and dr	ying of
No data.				
Product will be neutralized and coagulated by stomach acids. May irritate throat, stomach and esophagus.				
Excessive exposure to mists/vapors may irritate respiratory tract and result in headache and nausea.				
	n on Hazardous I CAS r* 111-9 78-51 Irritant. May cau and eyes. Slightly irritating Prolonged or re skin. No data. Product will be irritate throat, st Excessive expos	n on Hazardous Ingredient CAS# % r* 111-90-0 <6 78-51-3 <3 Irritant. May cause skin ar and eyes. Slightly irritating. Prolonged or repeated co skin. No data. Product will be neutralized irritate throat, stomach an Excessive exposure to mis	n on Hazardous Ingredients CAS# % OSHA (PEL) r* 111-90-0 <6 50 ppm 78-51-3 <3 N/E Irritant. May cause skin and eye irritation. and eyes. Slightly irritating. Prolonged or repeated contact may cause skin. No data. Product will be neutralized and coagulated irritate throat, stomach and esophagus. Excessive exposure to mists/vapors may in	n on Hazardous Ingredients CAS# % OSHA (PEL) TVL (ppm) r* 111-90-0 <6 50 ppm 50 ppm 78-51-3 <3 N/E N/E Irritant. May cause skin and eye irritation. Avoid contact wi and eyes. Slightly irritating. Prolonged or repeated contact may cause irritation and dr skin. No data. Product will be neutralized and coagulated by stomach ad irritate throat, stomach and esophagus. Excessive exposure to mists/vapors may irritate respiratory

in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4. First Aid	d Measures			
Eyes:	If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.			
Skin:	If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.			
Inhalation:	If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult, give oxygen and seek medical attention.			
Ingestion:	If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute remaining residue. Seek medical attention.			
5. Fire Fighting Measures				

# MSDS

Material Safety Data Sheet **1272** *Conforms to ANSI Z-400, 1-1993* Chemtel 24 Hour Emergency Response (800) 255-3924

# 1. Chemical Product and Company Identification

# MAINTEX

13300 East Nelson Avenue City of Industry, CA 91746 (800) 446-1888 Flash Point (F° TCC): >200°F

Auto-Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

# **Special Fire Fighting Procedures:**

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

## Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

#### 6. Accidental Release Measures

**Large Spills (55 gallons or more):** Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills: Mop up spill and rinse area.

7. Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

**Storage:** Store in a cool, dry place.

8. Exposure Controls/Personal Protection

Ventilation and Engineering Controls: None

Respiratory Protection: None

Protective Gloves: Rubber Gloves

Eye Protection: Chemical Splash Goggles

Boiling Point (F°): >212°F	Solubility In Water: Disperses	Odor: Slight Ammonia
Specific Gravity: 1.03	Volatiles (% by Wt.): 81	<b>pH:</b> 8 - 9
Appearance: Milky-white	Vapor Density: >1	<b>VOC:</b> <50 g/L
Evaporation Rate: <1	Vapor Pressure: <17 mm Hg	Freezing Point (F°): <32°F

Key: < means less than; > means greater than

These physical data are typical values based on material testing but may vary from sample to sample.

Typical values should not be constructed as a guaranteed analysis of any specific lot or specific item.

10. Stability and Reactivity			
Stability: Stable	Conditions to Avoid: Freezing		
Materials to Avoid: Strong Oxidizers			
Hazardous Decomposition Products: Oxides of carbon and nitrogen			
Hazardous Polymerization: Will Not Occur			

#### **11. Toxicological Information**

No Toxicology Information is available.

#### **12. Ecological Information**

No Ecological Information is available.

**13. Disposal Considerations** 

Waste Disposal Method: Dispose of waste in accordance with federal, state and local regulations.

14. Transport Information						
HAZMAT: No	Hazard Code: N/A	ID Numbe	er: N/A	Hazard Clas	<b>s:</b> N/A	
Hazardous Division: None				Packaging Group: N/A		
Hazardous Conte	nts: None					
15. Regulatory In	formation					
Proposition 65: N	lot Listed.					
* This product is subject to the reporting requirements of SARA Title III.						
EPA: No						
16. Other Informa	ation					
HMIS/NFPA Haza	rd Rating:	Health 1	Flammabi	lity 0	Reactivity 0	

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Maintex, Inc. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Maintex, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. For more information, contact Maintex, Inc.

#### MSDS Approval Date: 1/30/2007

For your safety, please ensure that you print and store all pages of this document together.