



RIVERSIDE CEMENT COMPANY

MATERIAL SAFETY DATA SHEET (MSDS) PORTLAND CEMENT

Section I – Identity

Manufacturer's Name and Address: RIVERSIDE CEMENT COMPANY, a California general partnership

Plant Locations: Crestmore Plant
1500 Rubidoux Boulevard (92509)
P. O. Box 832
Riverside, CA 92503
(909)774-2500

Terminal Locations: San Diego Terminal
920 Bay Marina Drive (91950)
P. O. Box 831
National City CA 92050
(619)474-5141

Oro Grande Plant
19409 National Trails Highway
P. O. Box 158
Oro Grande, CA 92368
(760)245-5321

Stockton Terminal
2845 W. Washington
Stockton, CA
(209)948-0529

Chemical Name and Synonyms: Hydraulic Cement. Portland Cement is also known as Hydraulic Cement (CAS #65997-15-1)

Trade Name and Synonyms: Type I, II, V Low Alkali, Plastic, Block, Rapid, Oil Well, White

MSDS Information: This MSDS issued in May, 2001 by the Environmental office and replaces any prior versions.

Section II – Chemical Data

Chemical Family:

Calcium Compounds. Calcium silicate compounds and other calcium compounds containing iron and aluminum make up the majority of the product.

Major Compounds:

3CaO.SiO ₂	Tricalcium silicate	CAS # 12168-85-3
2CaO..SO ₂	Dicalcium silicate	CAS # 10034-77-2
3CaO.Al ₂ O	Tricalcium aluminate	CAS # 12042-78-3
4CaO.Al ₂ O ₃ .Fe ₂ O ₃	Tetracalcium aluminoferrite	CAS # 12068-35-8
CaSO ₄ 2H ₂ O	Calcium sulfate dihydrate (gypsum)	CAS # 13397-24=5

Small amounts of CAO, MgO, Na₂SO₄, K₂SO₄ may also be present.

Formula:

Portland cement consists of finely ground portland cement clinker mixed with a small amount of calcium sulfate dihydrate (gypsum). The final product may also contain small amounts of liquid or solid grinding aids. Portland cement clinker is a sintered material produced by heating to high temperature (greater than 1200° Celsius) a mixture of substances such as limestone and shales, slag, clays or other natural occurring materials or recycled materials. The hydraulic compound manufactured is essentially hydraulic calcium silicates contained in a crystalline mass, not separable into the individual components.

Trace Elements: in less than .1% or ppm.

Trace amounts of naturally occurring chemicals might be detected during chemical analysis; some of which may be free crystalline silica, less than .1% and other trace constituents may include but not be limited to chromium, nickel compounds, titanium, manganese, phosphorus, vanadium and lead compounds, (in ppm levels.)

Hazardous Ingredients:

Portland cements are listed by OSHA in 29 CFR 1910.1000, Table Z-1-A, and require material safety data sheets (FR, January 19, 1989), MSHA (30 CFR 55.5.-1, Ref.2, ACGIH TLV's for 1973, Appendix E) and ACGIH (TLV's for 1984-85, Appendix D) list portland cements as nuisance dusts. NTP, LARC, or OSHA does NOT list Portland cements as carcinogens. It may, however, contain trace amounts of substances listed as carcinogens by these organizations. NTP, LARC, and OSHA do not list the grinding aids used in the manufacturing of portland cement at this facility as carcinogens.

The main hazardous ingredients of Hydraulic cement are:

Hydraulic cement – approximately 95% by weight
ACGIH TVL-TWA (1995-1996) = 10 mg. total dust/m³
OSHA PEL (8 hour TWA) = 50 million particles/ft³

Gypsum – approximately 5% by weight
ACGIH TVL-TWA (1995-1996) = 10 mg total dust/m³
OSHA PEL (8 hour TWA) = 10 mg total dust/m³
OSHA PEL (8 hour TWA) = 5 mg respirable dust/m³

Grinding agents – approximately 0.06% by weight
NTP, LARC, and OSHA do not list these grinding agents as carcinogens.

Section III – Physical Data

Boiling point:	Not applicable – portland cement is a powdered solid
Vapor pressure:	Not applicable – portland cement is a powdered solid
Vapor density:	Not applicable – portland cement is a powdered solid
Solubility:	Slight (0.1 – 1.0%)
Specific gravity (H ₂ O – 1)	3.15
Evaporation rate:	Not applicable – portland cement is a powdered solid
Appearance and odor:	Gray or white powder, no odor
Melting point:	Not applicable
pH in water (ASTM D 1293-95)	12 to 13

Section IV – Hazards Identification

Emergency Overview:

Portland cement is a light gray powder that poses little immediate hazard. A single short-term contact with the dry powder is not likely to cause serious harm. However, contact of sufficient duration with wet portland cement can cause serious, potentially irreversible tissue (skin or eye) damage in the form of chemical (caustic) burns, including third degree burns. The same type of destruction can occur if wet or moist areas of the body come in contact with dry portland cement.

Potential Health Effects:

Relevant routes of exposure:

Eye contact, skin contact, inhalation, and ingestion.

Effects resulting from eye contact:

Contact with airborne dust may cause immediate or delayed irritation or inflammation. Eye contact by larger amounts of dry powder or splashes of wet portland cement may cause effects ranging from moderate eye irritation to chemical burns and blindness. Such exposures require immediate first aid (see section V) and medical attention to prevent significant damage to the eye.

Effects resulting from skin contact:

Exposed persons may not feel discomfort until hours after a hazardous risk exposure has ended and significant injury has occurred. Consequently, the only effective means of avoiding skin injury or illness involves minimizing skin contact, particularly with wet cement.

Contact with dry portland cement may cause drying of the skin with consequent mild irritation or more significant effects attributable to aggravation of other conditions. Dry portland cement contacting wet skin or contact with moist or wet portland cement may cause more severe effects including thickening, cracking or fissuring of the skins. Prolonged contact can cause severe skin damage in the form of caustic chemical burns. Some individuals may exhibit an allergic response upon skin contact with portland cement. The response may appear in a variety of forms ranging from a mild rash to severe skin ulcers.

Effects resulting from inhalation:

Contact with portland cement may cause irritation to the moist mucous membranes of the nose, throat, and upper respiratory system. It may also leave unpleasant deposits in the nose.

Portland cement may contain trace amounts of free crystalline silica. Prolonged contact with respirable free crystalline silica may aggravate other lung conditions. It also may cause delayed lung injury including silicosis, a disabling and potentially fatal lung disease, and/or other diseases. Crystalline silica is now classified by IARC as a known human carcinogen (Group 1). NTP has characterized respirable silica as "reasonably anticipated to be a carcinogen".

Effects resulting from ingestion:

Although small amounts of dust are not known to be harmful, ill effects are possible if larger quantities are consumed. Portland cement should not be eaten.

Medical conditions which may be aggravated by inhalation or dermal exposure:

Pre-existing upper respiratory and lung diseases.
Unusual (hyper) sensitivity to hexavalent chromium salts.

Section V – First Aid

Eyes:

Immediately flush eyes thoroughly with water. Continue flushing eye for at least 15 minutes, including under lids, to remove all particles. Consult physician immediately.

Skin:

Wash skin with cool water and pH-neutral soap or a mild detergent intended for use on skin. Seek medical treatment in all cases of prolonged contact with wet cement, cement mixtures, liquids from fresh cement products, or prolonged wet skin contact with dry cement.

Inhalation or airborne dust:

Remove person to fresh air. Seek medical help if coughing and other symptoms do not subside. Inhalation of large amounts of portland cement requires immediate medical treatment.

Ingestion:

Do not induce vomiting. If conscious, have the victim drink plenty of water and seek medical attention immediately.

Section VI – Fire and Explosion Data

Flash point	Portland cement is non-combustible and non-explosive
Flammable and explosive limits:	Not applicable
Auto ignition temperature:	Not applicable
Extinguishing media:	Not combustible
Special firefighting procedures:	Not applicable
Hazardous combustion products:	Not combustible
Unusual fire and explosion hazards:	None

Section VII – Stability and Reactivity

Stability:	Stable. Keep dry until used.
Conditions to avoid:	Unintentional contact with water. Addition of water results in hydration and produces (caustic) calcium hydroxide.
Incompatibility:	When in contact with water, wet Portland cement is alkaline. As wetted, it is incompatible with acids, ammonium salts and aluminum metal. Reaction with these substances liberates hydrogen gas.
Hazardous decomposition:	Will not spontaneously occur.
Hazardous polymerization:	Will not occur.

Section VIII – Toxicological and Ecological Information

Ecotoxicity: No recognized unusual toxicity to plant and animals.

Section IX – Handling & Storage/Spill Prevention

Handling and storage:

Keep portland cement dry until used. Normal temperatures and pressures do not affect the material. Promptly remove clothing or clothing which is wet with cement fluids and launder before reuse. Wash thoroughly after contact with dust or wet cement mixtures or fluids.

Spill procedure:

Collect dry material using a scoop. Avoid cleanup methods that cause dust to become airborne. Avoid breathing the dust. Scrape up wet material and place in appropriate container. Allow the material to dry before disposal. Do not attempt to wash portland cement down drains. Emergency procedures are not required. Small amounts of material can be disposed of as common waste or returned to the original container for later use. Large volumes may require special handling. Dispose of waste material according to local, state and federal regulations.

Section X – Exposure Controls/Personal Protection

Skin protection:

Avoid contact with unhardened fresh Portland cement products. If contact occurs, wash affected area with soap and water. Where prolonged exposure to unhardened portland cement may occur, wear impervious, abrasion, and alkali-resistant gloves and boots, and protective clothing to eliminate skin contact. Where required, wear boots that are impervious to water to avoid foot and ankle contact. The use of barrier creams is advised. However, barrier creams should not be a substitute for gloves. After working with cement, workers should wash with a pH neutral soap. If clothing becomes saturated with wetted cement, it should be removed and replaced with clean, dry clothing.

Respiratory protection:

Avoid actions that can cause the cement dust to become airborne. Use local or general ventilation to control exposures below applicable exposure limits. Use NIOSH/MSHA (under 30 CFR 11) approved respirators in poorly ventilated areas. Note: Respirators and filters purchased after July 10, 1998 must be certified under 42 CFR 84.

Ventilation:

Use local exhaust or general dilution ventilation to control exposure within acceptable limits.

Eye Protection:

Wear safety glasses with side shields or tight fitting goggles. In extremely dusty environments, wear unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when working with portland cement or fresh cement products.

Section XI – Transportation Data

Hazardous materials description/proper shipping name:

Portland cement is not hazardous under U. S. Department of Transportation (DOT)

Hazard class:

Not applicable

Identification number:

Not applicable

Required label test:

Not applicable

Hazardous substances/reportable quantities (RQ):

Not applicable

Section XII – Other Regulatory Information

Status under USDOL-OSHA Hazard Communication Rule 29 CFR 1910.1200:

Portland cement is considered a “hazardous chemical” under this regulation as a nuisance dust and should be part of any hazard communication program.

Status under CERCLA/Superfund, 40 CFR 117 and 302:

Not listed

Hazard category under SARA (Title III), sections 311 and 312:

Portland cement qualifies as a “hazardous substance” with delayed health effects.

Status under SARA (Title III), Section 313:

Not subject to reporting requirements under Section 313

Status under TSCA (as of May 1997):

Some substances in portland cement are on the TSCA inventory list

Status under the Federal Hazardous Substances Act:

Portland cement is a “hazardous substance” subject to statutes promulgated under the act.

Status under California Proposition 65:

This product contains trace chemicals, including free crystalline silica, known to the State of California to cause cancer, birth defects, or other reproductive harm. California law requires the manufacturer to give the above warning in the absence of definitive testing to prove that the defined risks do not exist at levels of significance defined by the State.

Status under the Workplace Hazardous Materials Information System (WHMIS):

Portland cement is considered a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulation (Class E – Corrosive Material) and is therefore subject to the labeling and MSDS requirements of the WHMIS.

Section XIII – Abbreviations and Acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ASTM	American Society for Testing and Materials
CAS	Chemical Abstract Service
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
CFR	Code of Federal Regulations
DOT	Department of Transportation
FR	Federal Register
ft ³	Cubic foot (cubic feet)
LARC	International Agency for Research on Cancer
m ³	Cubic meter(s)
MSDS	Materials Safety Data Sheet
MSHA	Mine Safety and Health Administration
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limit
RQ	Reportable Quantity
SARA	Superfund Amendment and Reauthorization Act of 1986
TLV	Threshold Limit Volume

Status Under Workplace Hazardous Materials Information System (WHMIS), Canada:

Portland cement is considered to be a hazardous material under the Hazardous Products as defined by the Controlled Products Regulations (Class E – corrosive material) and is therefore subject to the labeling and MSDS requirements of the Workplace Hazardous Materials Information System (WHMIS)

Status Under Canadian Environmental Protection Act

Not listed

Section XIV – Other Information

Portland cement should only be used by knowledgeable persons. A key to using the product safely requires the user to recognize that portland cement reacts chemically with water, and that some of the intermediate products of this reaction (present while the cement is “setting” or “hardening” (and prior to being completely hard)) pose a far more severe hazard than does portland cement itself.

While the information provided in this MSDS is believed to provide a useful summary of the hazards of portland cement as it is commonly used, the MSDS cannot anticipate and provide all of the information that might be needed in every situation. Inexperienced product users should obtain proper training before using this product.

The data furnished in the MSDS does not address hazards that may be posed by other materials mixed with portland cement to produce portland cement products. Users should review other relevant MSDSs before working with portland cement or its products (i.e. portland cement concrete).

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY RIVERSIDE CEMENT COMPANY, except that the product shall conform to contracted specifications. The information provided herein was believed by RIVERSIDE CEMENT COMPANY to be accurate at the time of preparation or prepared from sources to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of product, and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based contract, breach of warranty, negligence or otherwise.