



LENMAR[®]

SAFETY DATA SHEET

Revision Date: 09-Jul-2015

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name MINERAL SPIRITS
Product Code 1A-137
Alternate Product Code TL9237
Product Class PAINT THINNER
Color Clear
Recommended use Paint thinner
Restrictions on use No information available

Manufacturer
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 800-225-5554
lenmar-coatings.com

Emergency Telephone Number(s)
CHEMTREC (US): 800-424-9300
CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Danger

Hazard statements

May cause cancer
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor

**Appearance** liquid**Odor** solvent**Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Do not breathe dust/fume/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces, no smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned get medical attention

Skin

If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water

Ingestion

If swallowed immediately call a POISON CENTER or physician
Do NOT induce vomiting

Fire

In case of fire use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight % (max)
Distillates, petroleum, hydrotreated light	64742-47-8	70
Stoddard solvent	8052-41-3	30

1,2,4-Trimethylbenzene	95-63-6	5
Naphthalene	91-20-3	0.5
Ethyl benzene	100-41-4	0.5
Cumene	98-82-8	0.5

4. FIRST AID MEASURES

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
Protection Of First-Aiders	Use personal protective equipment.
Most Important Symptoms/Effects	No information available.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Combustible material. Closed containers may rupture if exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors.
Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	Yes
Flash Point Data	
Flash Point (°F)	105
Flash Point (°C)	41
Flash Point Method	PMCC

Flammability Limits In Air

Lower Explosion Limit
Upper Explosion Limit

Not available
Not available

NFPA **Health:** 1 **Flammability:** 2 **Instability:** 0 **Special:** Not Applicable

NFPA Legend

0 - Not Hazardous
1 - Slightly
2 - Moderate
3 - High
4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Remove all sources of ignition.
Other Information	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Environmental Precautions	See Section 12 for additional Ecological Information.
Methods For Clean-Up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling	Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.
Incompatible Materials	No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Chemical Name	ACGIH	OSHA
---------------	-------	------

Stoddard solvent	100 ppm - TWA	2900 mg/m ³ - TWA 500 ppm - TWA
Naphthalene	10 ppm - TWA 15 ppm - STEL Skin	10 ppm - TWA 50 mg/m ³ - TWA
Ethyl benzene	20 ppm - TWA	100 ppm - TWA 435 mg/m ³ - TWA
Cumene	50 ppm - TWA	50 ppm - TWA 245 mg/m ³ - TWA prevent or reduce skin absorption

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment**Eye/Face Protection**

Safety glasses with side-shields.

Skin Protection

Long sleeved clothing. Protective gloves.

Respiratory Protection

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	solvent
Odor Threshold	No information available
Density (lbs/gal)	6.5 - 6.6
Specific Gravity	0.77- 0.79
pH	No information available
Viscosity (cps)	No information available
Solubility	No information available
Water Solubility	No information available
Evaporation Rate	No information available
Vapor Pressure	No information available
Vapor Density	No information available
Wt. % Solids	0 - 5
Vol. % Solids	0 - 5
Wt. % Volatiles	95 - 100
Vol. % Volatiles	95 - 100
VOC Regulatory Limit (g/L)	<800
Boiling Point (°F)	322
Boiling Point (°C)	161
Freezing Point (°F)	No information available
Freezing Point (°C)	No information available
Flash Point (°F)	105

Flash Point (°C)	41
Flash Point Method	PMCC
Flammability (solid, gas)	Not applicable
Upper Explosion Limit	No information available
Lower Explosion Limit	No information available
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition Coefficient (n-octanol/water)	No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions To Avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Contact with eyes may cause irritation.
Skin contact May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.

Ingestion	Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
Inhalation	High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.
Sensitization:	No information available.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target Organ Effects	No information available.
STOT - repeated exposure	No information available.
STOT - single exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	7070 mg/kg
ATEmix (dermal)	2901 mg/kg
ATEmix (inhalation-dust/mist)	75 mg/L

Component

Acute Toxicity

Distillates, petroleum, hydrotreated light

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3,000 mg/kg (Rabbit)

Stoddard solvent

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3160 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 6.1 mg/L (Rat)

1,2,4-Trimethylbenzene

LD50 Oral: 5000 mg/kg (Rat)

LC50 Inhalation (Vapor): 18000 mg/m³ (Rat, 4 hr.)

Naphthalene

LD50 Oral: 969 mg/kg (Rat)

LD50 Dermal: > 20,000 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 340 mg/m³ (Rat, 1 hr.)

Ethyl benzene

LD50 Oral: 3500 mg/kg (Rat)

LD50 Dermal: > 5000 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 55000 mg/m³ (Rat, 2 hr.)

Cumene

LD50 Oral: > 1400 mg/kg (Rat)

LD50 Dermal: 12300 µL/kg (Rabbit)

LC50 Inhalation (Vapor): 39000 mg/kg (Rat, 4 hr.)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen.:

Chemical Name	IARC	NTP	OSHA Carcinogen
Naphthalene	2B - Possible Human Carcinogen	Reasonably Anticipated Human Carcinogen	Listed
Ethyl benzene	2B - Possible Human Carcinogen		Listed
Cumene	2B - Possible Human Carcinogen		Listed

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information**Acute Toxicity to Fish**

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component**Acute Toxicity to Fish**Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic PlantsEthyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS**Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION**DOT**

Proper Shipping Name	Petroleum distillates, n.o.s.
Hazard Class	3
UN-No	UN1268
Packing Group	III
Description	UN1268, Petroleum distillates, n.o.s., 3, III,

In the US this material may be reclassified as a Combustible Liquid and is not regulated in containers of less than 119 gallons (450 liters) via surface transportation (refer to 49CFR173.120(b)(2) for further information).

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION**International Inventories****TSCA: United States**

Yes - All components are listed or exempt.

DSL: Canada

Yes - All components are listed or exempt.

Federal Regulations**SARA 311/312 hazardous categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>CERCLA/SARA 313 (de minimis concentration)</u>
1,2,4-Trimethylbenzene	95-63-6	5	1.0
Ethyl benzene	100-41-4	0.5	0.1
Naphthalene	91-20-3	0.5	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>Hazardous Air Pollutant (HAP)</u>
Ethyl benzene	100-41-4	0.5	Listed
Naphthalene	91-20-3	0.5	Listed
Cumene	98-82-8	0.5	Listed

State Regulations**California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

<u>Chemical Name</u>	<u>Massachusetts</u>	<u>New Jersey</u>	<u>Pennsylvania</u>
Stoddard solvent	X	X	X
1,2,4-Trimethylbenzene	X	X	X
Naphthalene	X	X	X
Ethyl benzene	X	X	X
Cumene	X	X	X

Legend

X - Listed

16. OTHER INFORMATION

HMIS **Health:** 1* **Flammability:** 2 **Reactivity:** 0 **PPE:** -

HMIS Legend

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
855-724-6802

Revision Date: 09-Jul-2015
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET