

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 10/17/2002

PAGE 1

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Company Name: ACE

TRADE NAME

ACE BOILED LINSEED OIL

REVISION DATE
10/02/2002

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

CARCINOGENICITY

SUBSTANCE DESCRIPTION	PERCENT	CAS#	NTP	ACGIH	OSHA	IARC
BOILED LINSEED OIL	95-100	8001-26-1	N	N	N	N

SECTION 3. REGULATORY INFORMATION

EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	REG. AGENCY	U/M	TWA	STEL	CEIL	SKIN	PEL
BOILED LINSEED OIL	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E

ADDITIONAL REGULATORY INFO

The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

CALIFORNIA (PROPOSITION #65)

Ingredients in this product are not listed on California's Prop 65 list: "Chemicals Known to the State to Cause Cancer or Reproductive Toxicity."

SEC. 313 SUPPLIER NOTIFICATION

The following information must be included in all MSDS that are copied and distributed for this material.

This product contains no chemicals subject to the reporting requirements of SARA III: Section 313.

CLEAN AIR ACT

This formula contains no known ozone depleting chemicals.

HAZARD COMMUNICATION STANDARD

This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 10/17/2002

PAGE 2

SECTION 3. REGULATORY INFORMATION
(CONTINUED)

The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.

SECTION 4. HAZARDS IDENTIFICATION

INHALATION ACUTE EXPOSURE EFFECTS

May cause irritation of respiratory tract, and cough.

SKIN CONTACT ACUTE EXPOSURE EFFECTS

None known.

EYE CONTACT ACUTE EXPOSURE EFFECTS

May cause irritation.

INGESTION ACUTE EXPOSURE EFFECTS

Inedible--not to be taken internally. May cause nausea, vomiting, and diarrhea.

CHRONIC EXPOSURE EFFECTS

None known.

MEDICAL CONDITIONS AGGRAVATED

None known.

PRIMARY ROUTE OF EXPOSURE

Inhalation, ingestion, and dermal.

SECTION 5. FIRST AID MEASURES

INHALATION

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

SKIN CONTACT

Irritation may result. Immediately wash with soap and water.

EYE CONTACT

Immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get medical attention.

INGESTION

Call your poison control center, hospital emergency room, or physician immediately for instructions.

NOTE TO PHYSICIAN

This formula is registered with POISINDEX.
Call your local poison control center for further information.

SECTION 6. FIRE FIGHTING MEASURES

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH	0	0
FLAMMABILITY	1	1
REACTIVITY	0	0
OTHER	A	NA

SECTION 6. FIRE FIGHTING MEASURES
(CONTINUED)

FLASH METHOD
TCC

FLASH POINT
250.00 F 121.11 C

LOWER EXPLOSION LIMIT
N/E

GENERAL COMMENTS
OSHA FLAMMABILITY: Class IIIB

EXTINGUISHING METHOD
Use carbon dioxide, dry powder, or foam.

FIRE FIGHTING PROCEDURES
Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

FIRE AND EXPLOSION HAZARDS
RISK OF FIRE FROM SPONTANEOUS COMBUSTION EXISTS WITH THIS PRODUCT. Oily rags or waste and other oily materials can cause spontaneous combustion fires if not handled properly. Immediately after use, and before disposal or storage, you MUST (1) Spread out all oily materials outside to dry by flattening them out to their full size in an airy spot for 24 hours at temperatures above 40 degrees F, or (2) Wash them thoroughly with water and detergent and rinse. Repeat until you have removed all oil from all cloths, tools, rags, paper, clothing, mops and any other materials contacted during use or as a result of an accidental spill. Make certain all wash and rinse water is disposed of down sink drain.

SECTION 7. ACCIDENTAL RELEASE MEASURES

CLEAN-UP

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. **SMALL SPILLS:** take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. **LARGE SPILLS:** dike far ahead of spill for later disposal.

For transportation related spills contact Infotrac at 1-800-535-5053 for emergency assistance.

WASTE DISPOSAL

Dispose in accordance with applicable local, state and federal regulations.

SECTION 8. HANDLING AND STORAGE

STORAGE

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

HANDLING

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

SECTION 9. TRANSPORT INFORMATION

TRANSPORTATION**No data available**

SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION PROTECTION

USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT. A dust mask does not provide protection against vapors.

RESPIRATORY PROTECTION

For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

SKIN PROTECTION

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

EYE PROTECTION

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

OTHER PROTECTION

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES

VOLATILE %

.2

by weight

BOILING POINT

343.00 F 172.77 C

VAPOR DENSITY (Air = 1.0)

Heavier than air

EVAPORATION RATE

Slower than ether

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 10/17/2002

PAGE 5

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES
(CONTINUED)

BULK DENSITY
7.747
lbs/gal at 75 F

pH FACTOR
N/E

PHOTOCHEMICALLY REACTIVE
NO

MAX V.O.C.
0 grams per liter

MAX VAPOR PRESSURE
0mm Hg at 20 degrees C

SECTION 12. STABILITY AND REACTIVITY

INCOMPATIBILITIES
Incompatible with strong oxidizing agents.

DECOMPOSITION
Decomposition may produce carbon monoxide and carbon dioxide.

POLYMERIZATION
Will not occur.

STABILITY
Stable.

SECTION 13. ADDITIONAL INFORMATION

IMPORTANT NOTE

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

LEGEND:

PPM = parts per million
MG/M3 = milligrams per cubic meter
N/E or NE = none established
GT = greater than
N/A or NA = not applicable
TCC = tag closed cup
TOC = tag open cup
PMCC = Pensky-Martens closed cup
IDLH = Immediately Dangerous to Life and Health

END OF MSDS